



SUR-2110FW240-24V

FLEXIBLE STRIP introduction

Product specification


Lister: 张敬华

Assessor: 张敬华

Approver: 丁春

Features:

- Available in 24V DC maximum.
- Very bright & low power consumption.
- Operating temperature: -20~50°C.
- Long life span LED lights, more than 50,000 hours+.
- Adhesive back, peel & stick!
- Dimmable by controller or sensor switch.
- Waterproof, IP20




Applications:

Ideal for sign letters and channel letters, concealed lights, room lighting, equipment.

Assembly drawing

Top View




Section



Parameter:

SMD 2110, 240LED/Meter								
Model No.	Size(mm)	Color	Cut Every (LEDS)	LEDS/M	Lumen/M	Voltage	Power/M	Package
SUR-2110FWW240-24V	L5000*W4*H1.5	WW 	6	240	439	24V	6W	5Meters/Reel
SUR-2110FNW240-24V		NW 			459			
SUR-2110FCW240-24V		CW 			473			


Radiation diagram



Relative luminous intensity Iv %


LED Light distribution





How to connect flexible strip

Below shows you how to connect the flexible strip to power supplies.



Package:



1 reel/bag



25 bags/Inner Box

Inner box
size:25x26x31cm



50 Bags/Outer Box





Outer box
size:34x52x27cm




Package: 5 meter strip in one reel, one reel in one anti-static bag, 25 bags put into one inner box, 2 inner box put into one carton.

! Cautions :

When install the led strip, please note the installation technique. The led strip can be bent, but not distorted, as shown below:



Distortion(Wrong)



Bend (Right)