


### Functions

Model	TD010
Operation	Switch ON/OFF with dimming and memory with brightness buffer in 3 seconds
Input Voltage	12V–24V DC
Output Voltage	12V–24V DC
Input Current	8A
Height of Spring	20mm
Load Around	96W for 12V, and 192W for 24V

### Connection Diagram




Touch switch ON/OFF with dimming and 0V memory.

### Operations

- The conductive spring needs to be covered by insulation material such as glass, plastic or ceramic material, thickness ≤ 3mm.
- Originally “OFF” when the power is connected.
- Quick touch (time is less than 550ms) can turn the light on and off. Touch to turn on with brightness buffer in 3 seconds; another touch to turn off with brightness buffer in 3 seconds. The lamp is 90% bright when it is on.
- Hold on touching (time is above 550ms) can adjust the brightness endlessly. The brightness will be reduce or increase with brightness buffer.
- Quick touch and hold on touching can be chosen anytime without any collision.
- This sensor will memorize the status of the dimming in DC12V-24V.

### Installation Steps



**Note:** The function/program can be customized, made upon different needs, such as longer time for stay on, etc.


## Recommended Profiles/Optional

Model	Color	Size(mm)	Length	Drawing	Photo	Installation
A1707	White	17.4*82	1-3m			Surface mounting
A2507	Black	23.7*8.2	1-3m			Recessed mounting
F003	Aluminum	19.71*7.61	1-3m			Surface mounting


## Recommended Strips/Optional

### General description

- Available in 12/24V DC maximum
- CRI80 & CRI90 LED Strip are available
- Working temperature: -20°C to +50°C
- Very bright & low power consumption
- Long life span LED lights, more than 50,000 hours
- Adhesive back, peel & stick
- IP20, IP65, IP67 are available



Color Spectrum (CRI90)



### Electronic & Output Data

#### SMD2835, 60 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W8*H1.5	WW <input checked="" type="checkbox"/>	90+		60	1000	12/24	14.4	5
	NW <input type="checkbox"/>				1100			
	CW <input type="checkbox"/>				1200			

#### SMD2835, 120 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W10*H1.5	WW <input checked="" type="checkbox"/>	90+		120	1300	12/24	14.4	5
	NW <input type="checkbox"/>				1400			
	CW <input type="checkbox"/>				1500			

#### SMD2110, 280 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W10*H1.5	WW <input checked="" type="checkbox"/>	90+		280	1420	24	19.2	5
	NW <input type="checkbox"/>				1460			
	CW <input type="checkbox"/>				1510			