


Functions

Model	TD005
Operation	ON/OFF + dimming function.
Input Voltage	12V-24V DC
Output Voltage	12V-24V DC
Input Current	4A
Load Around	48W for 12V, and 96W for 24V


Connection Diagram




Operations

- Originally "Off" when the power is connected.
- Quick touch (time is less than 550ms) can turn ON/OFF the light. One touch to turn on; touch again to turn off. The lamp is 90% bright when it is on.
- Hold on touching (time is above 550ms) can adjust the brightness endlessly. It will reduce the brightness endlessly to the minimum in 3 seconds holding on when the light is on. It will increase the brightness endlessly to 100% in 3 seconds holding on when the light is off.
- Quick touch and hold on touching can be chosen anytime without any collision.


Installation Steps




1 Stick the 3M tape on the sensor switch



2 Fixed the sensor onto the cabinet






3 Connect to the power supply



4 Working status


Recommended Profiles/Optional

Model	Color	Size(mm)	Length	Drawing	Photo	Installation
A1707	White	17.4*82	1-3m			Surface mounting
A1715	Black	17.4*15.7	1-3m			Surface mounting
A1920	Aluminum	19.9*18.5	1-3m			Surface mounting


Recommended Strips/Optional

General description

- Available in 12/24V DC maximum
- CRI80 & CRI90 LED Strip are available
- Working temperature: -20°C to +50°C
- Very bright & low power consumption
- Long life span LED lights, more than 50,000 hours
- Adhesive back, peel & stick
- IP20, IP65, IP67 are available



Color Spectrum (CRI90)



Electronic & Output Data

SMD2835, 60 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W8*H1.5	WW 	90+		60	1000	12/24V	14.4	5
	NW 				1100			
	CW 				1200			

SMD2835, 120 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W10*H1.5	WW 	90+		120	1300	12/24V	14.4	5
	NW 				1400			
	CW 				1500			

SMD2110, 280 LEDs/m

Size (mm)	Color	CRI	Photo	LED Qty/m	Lumen/m	Voltage (V)	Power (W/m)	Packing (m/reel)
L5000*W10*H1.5	WW 	90+		280	1420	24V	19.2	5
	NW 				1460			
	CW 				1510			