


Functions

| | |
|------------------|---|
| Model | TD002 |
| Operation | Touch switch ON/OFF with dimming function |
| Input Voltage | 12V–24V DC |
| Output Voltage | 12V–24V DC |
| Input Current | 8A |
| Height of Spring | 20mm |
| Load Around | 96W for 12V, and 192W for 24V |


Connection Diagram



Operations

- The conductive spring needs to be covered by insulation material, such as glass, plastic or ceramic material (Thickness≤3mm).
- Non-memory touch switch performs as below:
 - ① Originally Off when the power is connected.
 - ② Quick touch (Time is less than 550ms) can turn ON/OFF the light. One touch to turn on; touch again to turn off. The lamp is 90% bright when it is on.
 - ③ Hold on touching (Time is above 550ms) can adjust the brightness endlessly. It will reduce the bightness endlessly to the minimum in 3 seconds holding on when the light is on. It will increase the brightness endlessly to 100% in 3 seconds holding on when the light is off.
 - ④ Quick touch and hold on touching can be chosen anytime without any collision.

Installation Steps



Note: The function/program can be customized, made upon different needs, such as longer time for stay on, etc.


Recommended Profiles/Optional

| Model | Color | Size(mm) | Length | Drawing | Photo | Installation |
|-------|----------|------------|--------|---------|-------|-------------------|
| A1707 | White | 17.4*82 | 1-3m | | | Surface mounting |
| A2507 | Black | 23.7*8.2 | 1-3m | | | Recessed mounting |
| F003 | Aluminum | 19.71*7.61 | 1-3m | | | Surface mounting |


Recommended Strips/Optional

General description

- Available in 12/24V DC maximum
- CRI80 & CRI90 LED Strip are available
- Working temperature: -20°C to +50°C
- Very bright & low power consumption
- Long life span LED lights, more than 50,000 hours
- Adhesive back, peel & stick
- IP20, IP65, IP67 are available



Color Spectrum (CRI90)



Electronic & Output Data

SMD2835, 60 LEDs/m

| Size (mm) | Color | CRI | Photo | LED Qty/m | Lumen/m | Voltage (V) | Power (W/m) | Packing (m/reel) |
|---------------|--|-----|-------|-----------|---------|-------------|-------------|------------------|
| L5000*W8*H1.5 | WW <input checked="" type="checkbox"/> | 90+ | | 60 | 1000 | 12/24 | 14.4 | 5 |
| | NW <input type="checkbox"/> | | | | 1100 | | | |
| | CW <input type="checkbox"/> | | | | 1200 | | | |

SMD2835, 120 LEDs/m

| Size (mm) | Color | CRI | Photo | LED Qty/m | Lumen/m | Voltage (V) | Power (W/m) | Packing (m/reel) |
|----------------|--|-----|-------|-----------|---------|-------------|-------------|------------------|
| L5000*W10*H1.5 | WW <input checked="" type="checkbox"/> | 90+ | | 120 | 1300 | 12/24 | 14.4 | 5 |
| | NW <input type="checkbox"/> | | | | 1400 | | | |
| | CW <input type="checkbox"/> | | | | 1500 | | | |

SMD2110, 280 LEDs/m

| Size (mm) | Color | CRI | Photo | LED Qty/m | Lumen/m | Voltage (V) | Power (W/m) | Packing (m/reel) |
|----------------|--|-----|-------|-----------|---------|-------------|-------------|------------------|
| L5000*W10*H1.5 | WW <input checked="" type="checkbox"/> | 90+ | | 280 | 1420 | 24 | 19.2 | 5 |
| | NW <input type="checkbox"/> | | | | 1460 | | | |
| | CW <input type="checkbox"/> | | | | 1510 | | | |