

SUR-MINI-TR Series 10mm 24V low voltage Mini Track system

Magnetic Spotlight

Source: Shopify product specification table for surmountor.myshopify.com

Model Number	Product Name	Description
MINI-TR01S	Power Track	Surface-mounted with Clip-on Design Surface processing: Spraying surface 2-Conductor Pure Copper Busbar Size: L1000*W15*H10mm L2000*W15*H10mm
MINI-TR01C	Corner-mounted with Clip-on Design	Surface processing: Spraying surface 2-Conductor Pure Copper Busbar Size: L1000*W35.2*H10mm L2000*W35.2*H10mm
MINI-TR01R	Recessed Installation	Surface processing: Spraying surface 2-Conductor Pure Copper Busbar Size: L1000*W17.6*H12.3mm L2000*W17.6*H12.3mm
MINI-TR-POWER	Power Input Module	Integral Power Source Voltage: DC24V Watt: 80W Size: $\Phi 74$ *H35.5mm
MINI-TR02	Power Input Cable Input	Conductive Module Connector
MINI-TR02LW	Power Track Connector Components	L Shape Connector with Wire Vertical Conductive Module Cable Connector
MINI-TR02I	I-Shaped Connector	Straight-Through Conductive Module Connector
MINI-TR02L	L-Shaped Connector	Corner Conductive Module Connector
MINI-TR02T	T-Shaped Connector	Three-Way Conductive Module Connector
MINI-TR02X	X-Shaped Connector	Four-Way Conductive Module Connector
MINI-TR-FL	LED Lighting Components	Flood Light Voltage: DC24V Power: 6W Size: L231.3*W11.8*H19.5mm CCT: 3000K/4000K/6000K Lumen: 250LM/260LM/255LM
MINI-TR-GL (3W)	Grille Light	Voltage: DC24V Power: 3W Size: L117.3*W11.8*H19.5mm CCT: 3000K/4000K/6000K Lumen: 190LM/200LM/195LM Beam Angle: 15°/24°/36°
MINI-TR-GL (6W)	Grille Light	Voltage: DC24V Power: 6W Size: L231.3*W11.8*H19.5mm CCT: 3000K/4000K/6000K Lumen: 380LM/400LM/395LM Beam Angle: 15°/24°/36°
MINI-TR-FGL	Fold Grille Light	Voltage: DC24V Power: 3W Size: L117*W11.8*H33mm CCT: 3000K/4000K/6000K Lumen: 170LM/180LM/175LM Beam Angle: 15°/24°/36°
MINI-TR-SL	Spot Light	Voltage: DC24V Power: 2W Size: $\Phi 18$ *40mm CCT: 3000K/4000K/6000K Lumen: 115LM/120LM/118LM Beam Angle: 15°/24°/36°
MINI-TR-SDL	Spot Double Light	Voltage: DC24V Power: 2.5W Size: $\Phi 15$ *29mm CCT: 3000K/4000K/6000K Lumen: 160LM/170LM/165LM Beam Angle: 15°/24°/36°
MINI-TR-BSL	Big Spot Light	Voltage: DC24V Power: 2.5W Size: $\Phi 30$ *65mm CCT: 3000K/4000K/6000K Lumen: 180LM/190LM/185LM Beam Angle: 15°/24°/36°
MINI-TR-CSL	Circle Spot Light	Voltage: DC24V Power: 3W Size: L79*W20*H87mm CCT: 3000K/4000K/6000K Lumen: 250LM/265LM/260LM Beam Angle: 15°/24°/36°